



NO.	Description	Material	QTY.
46	Heat-shrinkable Tube	∅2.5×20	1
45	Rivet	Cu	1
44	terminal	Cu	1
43	Switch Supporter	Epoxy	1
42	Stationary Contact	Cu-Ag	1
41	Move Contact	Cu	1
40	Connector	CE2	1
39	Heat-shrinkable Tube	∅4/20mm	1
38	Heat-shrinkable Tube	∅4/40mm	2
37	Internal Wire	UL1007/130mm	2
36	Current Fuse	1A	1
35	Switch		1
34	Screw	ST2.5×6	1
33	Spring	65Mn ∅0.6	1
32	Slef Lock	PA66+30%gf	1
31	Spring	65Mn	1
30	Botton	ABS	1
29	Top Enclosure	PP	1
28	Feet	PVC	4
27	Screw	ST3x6	3
26	power supply cord		1
25	Screw	ST3x10	3
24	Cord Clamp	ABS	1
23	Screw	M3x6	2
22	Bottom	PP	1
21	Washer	Epoxy ∅10.5×12×0.5	3
20	Gear	POM	1
19	C-ring	65Mn ∅4.7	1
18	Gear	POM	1
17	Gear insert	Fe PM	1
16	Gearig shaft	Fe ∅3	1
15	Bearing	∅5×∅11.5×12.8	1
14	Motor Plate	ABS	1
13	Driving gear	Fe	1
12	Motor	SR5512	1
11	Screw	ST3x12	8
10	Main Enclosure	PP	1
9	Waher	Epoxy ∅10.5×12×0.5	2
8	Driving Shaft	SS-SPCC	1
7	Cup	PS	1
6	Blade(down)	SUS202	1
5	Washer	ABS	1
4	Blade support	ABS	1
3	Blade(up)	SUS202	1
2	Rivet	AL ∅3×13.5	4
1	Lid	PS	1
NO.	Description	Material	QTY.